

Raynox Lens Compatible Table for FUJIFILM FinePix HS20EXR/HS22EXR

Model	Magnification	Required Adapter	Image Captured	Distance to the Object/ Minimum shooting distance	Effective Zooming without vignetting (4:3 Still mode)
DCR-2025PRO	2.2x	RA6258(included)		About 12m	17-30x
DCR-1541PRO	1.54x	RA5258A		About 6m	10-30x
HDP-2800ES	0.28x	RA5258A		About 1cm	1-3x
DCR-7900ZD	0.79x	Direct mount(58mm)	**	About 1cm	Use at the max.wideangle position
DCR-150	4.8-diopter	UAC-2000(included)	10.9mm*	210mm (Focusing set at infinity)	8-30x
DCR-250	8-diopter	UAC-2000(included)	6.5mm*	109mm (Focusing set at infinity)	8-30x
MSN-202	25-diopter	UAC-3500(included)	2mm*	32mm (Focusing set at infinity)	15-30x
MSN-505	32-diopter	UAC-3500(included)	1.6mm*	18.5mm (Focusing set at infinity)	17-30x

The focal length of HS20EXR/HS22EXR: 4.2mm-126mm (24mm-720mm in equivalent of 35mm film format)

*The size of width captured on full LCD screen.

** Slight vignetting may occurred in some cases.